## **SPA/RSA SERIES**

## SPA/RSA Process Analyzer Sample Probe Assembly (SPA) with a Conax Packing (PG) Compression Seal Fitting

#### **Features & Options**

- Plasma welded stop collar
- Retaining Chain Kit, required as a safety measure
- Wake frequency calculations
- Various probe ends and valve types available

## **For Unique Applications**

- Process analyzing
- Flare stack emissions
- Chemical injection quills
- Waste water analysis
- Potable water quality sampling
- Hot tapping liquid or gas streams



Retaining Chain Kit



## **Sample Probe Assembly**

The Conax Technologies' Sample Probe Assembly (SPA) is used to hot-tap a probe into a process through a process isolation valve.

## **Temperature and Pressure Ratings**

Refer to the appropriate sections of this catalog for temperature and pressure ratings for static conditions. Pressure ratings are reduced when the seal fitting cap is loosened to allow for the insertion or extraction of the sample probe.

## **Material Options**

- Optional materials for the Sample Probe Assembly and the Conax Technologies' PG Fitting body (wetted components) are available. Available options include 316L SST, 316 NACE SST, 316L CRN, MONEL<sup>™</sup> 405, HASTELLOY<sup>™</sup> C276 and INCONEL<sup>™</sup> 600.
- Sample Probe Assemblies and/or PG Fitting bodies can be supplied with a Silcolloy™ 1000 (Silcosteel™-CR) or SilcoNert™ 2000 (Siltek™/Sulfinert™) coating.
- Standard Sealants are Teflon<sup>™</sup>, PEEK<sup>™</sup>, and GraFoil<sup>™</sup>. Other sealants are available for special applications.

#### How to Configure the Model Number of an SPA Assembly

Standard Conax Packing (PG) Compression Seal Fitting model numbers and configurations apply. Compression seal fittings are supplied loose unless otherwise indicated.

#### Example model number: SPA/PG5-500-A-T/500X120W(S304)-45-1-36

Sample Probe <b>Configurator</b>														
Product Name	Compression Seal Fitting Used if none indicate "X"	Tube OD	Tube Wall	Tube Material (S304 or S316, M405, HC276, I600)	A Tube End Angle (90 °, 60 °, 45 °, 30 °)	B Dimension (1/4" increments 1 = 1/4")	L Overall Tube Length (inches)							
SPA	PG5-500-A-T	500	120W	S304	45	1	36							
Standard diame welded stop co larger than the probe. Special s available upon	eter for the Illar is 0.125" sample sizes request.	- 0.25" (6.	35) "L" —											

#### Standard Tube Sizes\* (Please refer to bulletin 6066DS.)

Standard	<b>Tube</b>	Sizes				Standar	Standard Tube Sizes								
OD (mm)	Wall (in)	Wall (mm)	ID (in)	ID (mm)	Material	OD (mm)	Wall (in)	Wall (mm)	ID (in)	ID (mm)	Material				
0.250" (6.35)	0.025"	0.64	0.200″	5.08	S304	0.500" (12.70)	0.035″	0.89	0.430"	10.92	S304				
	0.035"	0.89	0.180″	4.57	S304		0.040"	125	0.402"	10.21	5201				
	0.025″	0.64	0.200"	5.08	S316		0.049	1.2.5	0.402	10.21	5504				
	0.035″	0.89	0.180″	4.57	S316		0.065"	1.65	0.375"	9.53	S304				
	0.035"	0.89	0.180″	4.57	MONEL <sup>™</sup> 400		0.120"	3.05	0.260"	6.60	S304				
	0.035"	0.89	0.180″	4.57	Hast C276		0.049"	1.25	0.402"	10.21	S316				
0.375" (9.53)	0.040"	1.02	0.295″	7.49	S304		0.065″	1.65	0.370"	9.40	MONEL™ 400				
	0.065″	1.65	0.245"	6.22	S304										
	0.040"	1.02	0.295″	7.49	S316		0.049"	1.25	0.402″	10.21	Hast C276				
	0.058″	1.47	0.259"	6.58	S316	0.625" (15.88)	0.065″	1.65	0.495″	12.53	S304				
	0.065"	1.65	0.245″	6.22	MONEL <sup>™</sup> 400	0.750" (19.05)	0.095″	2.41	0.560″	14.22	S316				
	0.035"	0.89	0.305″	7.75	Hast C276		0.065″	1.65	0.620"	15.75	MONEL™ 400				
	0.065″	1.65	0.245"	6.22	Hast C276	1000" (25.40)	0.120"	3.05	0.760"	10 30	5716				

\*Tubing is seamless or welded and annealed.

## **Conax PG Compression Seal Fittings**

PG Series C	ompre	essior	ı Seal	Fittin	gs												
			Sample Pro	be Tubing D	iameter in i	nches (mm)		Sample Probe Pipe Diameter in inches (mm)									
Model	NPT Size (in)	0.250 (6.35)	0.375 (9.53)	0.500 (12.70)	0.625 (15.88)	0.750 (19.05)	1.000 (25.40)	1/8" 0.405" OD (10.29)	1/4" 0.54" OD (13.72)	3/8" 0.675" OD (17.15)	1/2" 0.84" OD (21.34)	3/4" 1.05" OD (26.67)	1″ 1.315″ OD (33.40)	1.25" 1.66" OD (42.16)	1.50" 1.90" OD (48.25)		
PG2	1/4″	Х															
PG4	1/2"	Х	Х					Х									
PG5 (PTM4)	1/2"	Х	Х	Х				Х	Х								
PG5	3/4"	Х	Х	Х	Х	Х		Х	Х	Х							
PG5 (PTM6)	1″	Х	Х	Х	Х	Х		Х	Х	Х							
PG6	1″					Х	Х				Х						
PG7	1-1/4″										Х	Х	Х				
PG8	1-1/2"												Х				
PG9	2"													Х	Х		

Other sizes and materials available upon request. All Conax PG Fittings are available with an optional welded or threaded ASME/ANSI Raised-face Flange mount.

## Retractable Sensor Assembly (RSA) with Conax PG Compression Seal Fitting



## **Features and Benefits**

- Complete factory engineered and assembled designs
- RTD and Thermocouple designs
- Plasma welded stop collar
- Retaining Chain Kit, required as a safety measure
- Wake Frequency Calculations available on request
- Available in Direct Immersion (see photo) or Retractable Thermowell Designs
- Various materials are available for the sensor sheath, thermowell and the Conax PG Compression Seal Fitting body

## Improved Design—Superior Performance

Conax Technologies has designed an innovative and unique approach to inserting and extracting a temperature sensor into a pressurized process through a process isolation valve in conjunction with a Conax Compression Seal Fitting.

The Conax Retractable Sensor Assembly (RSA) is specifically designed for applications requiring the insertion and extraction of a temperature sensor in process pipelines, flare stack emissions and storage tanks.

## **Temperature and Pressure Ratings**

Please refer to the appropriate sections of Conax Catalog 5001 for temperature and pressure ratings for static conditions. Pressure ratings are reduced when the seal fitting cap is loosened to allow for the insertion or extraction of the RSA.

## **Retaining Chain Kit**

The Conax retaining chain kit is constructed from stainless steel and is specifically designed to function with the Conax RSA Compression Seal Fitting. This kit is required as a safety measure.

## **Technical Sales Support**

Conax Technologies' Technical Team can help you solve your problems. Call our inside sales team and you'll get the support you need to make the right choices.

# Ensure your SPA meets ASME and IEC standards with our online calculator

To help ensure you're choosing the proper Sample Probe Assembly (SPA) for a specific application, we created the Conax Technologies Wake Frequency Solution Builder<sup>™</sup> our user-friendly online calculator.

This tool enables you to enter data for the specific SPA you need and receive immediate calculation results, based on ASME PTC 19.3 TW-2010 and/or IEC/TR 61831 standards. If there are problems with the configuration of your SPA, you'll see exactly what needs to be adjusted. If the design is approved, you'll see confirmation that each element tested has passed, and you can contact Conax to purchase the SPA.

The Wake Frequency Solution Builder<sup>™</sup> provides you with an instant pass or fail rating online. And you'll receive comprehensive Sample Probe Design Calculation Datasheets based on ASME PTC 19.3 TW-2010 and/or IEC/TR 61831 calculations with your SPA order at no additional charge. We understand there may be times when you'll need a higher level of help, so we've included a button on the calculator page that enables you to request help.

## **Retaining Chain Kit**



**18-0005-XXXN-XX-XX:** Base design Retaining Chain Kit Assembly.

**18-0037-XXXN-XX:** Retaining Chain Kit Assembly for high vibration applications with a Retaining Washer plasma welded to the Sample Probe Collar.

## Installation Instructions for the Conax Retaining Chain Kit

#### To Install Shaft Collars:

- 1. Loosen collar screws
- 2. Place collar or welded collar/washer (Item 2) and shaft collar (Item 3) over probe as shown.
- 3. Position collar (Item 3), tight against (Item 2) washer such that there are no visible gaps.
- 4. Tighten collar screws.
  - For 0.250" probe, tighten to 8 in-lbs
  - For 0.375" probe, tighten to 15 in-lbs
  - For 0.500" probe, tighten to 28 in-lbs
  - For 0.625" probe, tighten to 45 in-lbs
  - For 0.750" & 1.000" probes, tighten to 110 in-lbs
  - Please consult factory for other sizes.

#### To Adjust Safety Chain:

- 1. Unscrew threaded connector (Item 5) link at process side of probe.
- 2. Take up all extra chain links and loop over the threaded connector.
- 3. Screw threaded connector back together and wrench tighten (5 in-lbs recommended).



#### **User Cautions**

## **Sample Probe Assembly**

- The end user must take the necessary safety precautions when loosening the cap of the Conax PG Fitting when inserting or extracting the Sample Probe into pressurized environments.
- The end user is responsible to control any leakage of process that may occur during insertion or extraction of the Sample Probe.
- The end user is responsible for determining the appropriate Sample Probe material, diameter and wall thickness for the process environment and flow rates.
- Conax Technologies is not responsible for the operation of the Conax PG Fitting assembly once the cap is loosened to allow for the insertion or extraction of the Sample Probe.
- Typically, when properly installed, the angled Sample Probe tip should have the long side upstream. This reduces the particulates entering the Sample Probe and into the process analyzer filter.
- The Sample Probe immersion length should be designed to obtain a process sample close to the center third of the pipe.
- It is suggested that the end user mark the Sample Probe end with an indelible ink marker relative to the angled end for proper orientation into the process.

#### **Retaining Chain Kit**

- Retaining chain assembly is not intended to assist or control the insertion/extraction of the sample probe. The operator is responsible for restraint of the sample probe at all times.
- Chain must be kept as short as possible to function properly. Some minor slack in the chain will be present when sample probe is inserted. The retaining chain kit is not intended for impact loads. If it is subject to an impact load, all parts must be inspected/replaced as required.
- Periodically inspect restraint system. Re-torque probe collar and threaded connector. Replace parts as necessary.
- Maximum design pressure for the retaining chain kit is 500 PSIG. ( $\leq$  .500" (12.70 mm) Sample Probe diameter).
- Prior to installing the PG Fitting into the process valve port, install the front retaining washer (Item 1) over the PG Fitting pipe thread.



Retaining Washer plasma welded to the Sample Probe Collar.



Note: After the Sample Probe is properly inserted and the Conax PG Fitting is properly assembled and tightened to the recommended factory torque requirement, ensure the chain length is as short as possible using the Threaded Connectors. This requires the qualified user to adjust the chain prior to loosening the PG Fitting cap to allow retraction of the Sample Probe.

Refer to Conax PG Compression Seal Fitting Assembly Instructions Bulletin 6026 Rev D as supplied with shipment or available at http://www.conaxtechnologies.com/product/ assembly-instructions-fittings-feedthroughs.

 ·····
 · · · · · · · · · · · · · · · · · · ·
 ·····
 · · · · · · · · · · · · · · · · · · ·
 ·····
 · · · · · · · · · · · · · · · · · · ·

Chico™ is a trademark of Crouse-Hinds™ CSA™ is a trademark of Canadian Standards Association™ GraFoII™ is a trademark of NeoGraf Solutions™ HASTELLOY™ is a trademark of HAYNES InternationaI™ INCONEL™ is a trademark of Special Metals™ Kapton™ is a trademark of E.I. du Pont de Nemours and Company™ Kevlar™ is a trademark of E.I. du Pont de Nemours and Company™ MONEL<sup>™</sup> is a trademark of Special Metals<sup>™</sup> NEC<sup>™</sup> is a trademark of National Fire Protection Association<sup>™</sup> PEEK<sup>™</sup> is a trademark of Victrex<sup>™</sup> Silcolloy<sup>™</sup> is a trademark of SilcoTek<sup>™</sup> Silcosteel<sup>™</sup> is a trademark of SilcoTek<sup>™</sup> Silcsteel<sup>™</sup> is a trademark of SilcoTek<sup>™</sup> Sulfinert<sup>™</sup> is a trademark of SilcoTek<sup>™</sup> TefIon<sup>™</sup> is a trademark of The Chemours Company<sup>™</sup> TefIcel<sup>™</sup> is a trademark of The Chemours Company<sup>™</sup> ULTEM<sup>™</sup> is a trademark of Shpp Global Technologies<sup>™</sup> Vespel<sup>™</sup> is a trademark of E.I. du Pont de Nemours and Company<sup>™</sup> Viton<sup>™</sup> is a trademark of The Chemours Company<sup>™</sup>



# **Sample Probe Assembly Quote Request Form**

1-OVERALL DIMENSIONS		CONTACT INFORMATION		9-PROBE END OPTI	ONS	
"L" Overall Sample Probe Length		Company			Plain End	
"B" Stop Collar Set-Back	(.25" is std.)	Completed By		Plain End w/	laser markings	
"Y" Flange/Nozzle/Valve Length		Email Address		V-Notch Relativ	e to Angle "A"	
"Z" Immersion Into Process Flow		Phone			Integral NPT	
"X" Existing Projection Nozzle Length		Quantity		Tube E	nd Fitting NPT	
<b>2</b> ANCLE "A"		"L"		Other, please specify:		
	"7"	"    "Y" (1)				
	< <u> </u>	$\rightarrow$				
	"B" ①→  ←			<b>10</b> -CONAX PG SEAL	FITTING (S	ee page 2)
STOP COLLAR*	Angle "A" 2			Temperature at PG Seal Fitting		
Yes	Stop Collar 3			NPT		
No				Socket Weld	Dia.:	Length:
Special (Detail Needs):	(4)			Threaded Flange	Size:	Rating:
* Standard Woldod Ston Collar is 125"	Process Flow	Nozzle Flange/ Valve Bonda Conax Nipple Relief/ PG Seal	Chain Kit Sample Probe Probe End	Welded Flange	Size:	Rating:
larger than the Sample Probe		Counterbore Fitting		Wetted (PG Body) Materials R	equirement	
				303 SST	MONEL 400	
4–PROCESS CONDITIONS	5-PROJECTION NOZ		6-SAMPLE PRODE/OPTIONS			
(Please provide all units of measure)	Pipe Size		Material		HASTELLUT	
Media	(or wall thickness)		Probe (tube) OD: Wall:	316 NACE	HASTELLOY C	276 🛄
Velocity Ft/Se	C Min. Through	7—VALVE	Probe (pipe)	Other, please specify:		
Temperature °F or °	C Existing	By Conax 🔲	Coatings/ Silcolloy™ 1000			
Pressure	SI New/Planned	By other				
Viscosity c	P	Through bore if by	-   SilcoNert™ 2000 (Siltek®/Sulfinert®) □			
Density LB/f	Wake Frequency Calculations	others or existing		II-SPECIAL SEAL FI	TING BOD	Y DESIGN
Process Pipe Size	Solution Builder™ website at	Size	Electro-Polish	Bonda Relie	ef/Counterbore	
(or wall thickness)	<u>ConaxTechnologies.com/wak</u> <u>frequency-solution-builder</u>	e- Ball	Not Required		ntegral O-Ring	
		Type (check all Gate			Dual Sealant	
		Socket weld x NPT		L		J
		Material and/or special needs:	1			
• Place print complete and	return to Conov					
Prease print, complete and Prease print, complete and	mela Droho Assombly				OÍ	<b>AX</b>
brochure at our website				TEC	HNOL	OGIES
				seebl	Solution	SUCCOS

## How to Configure the Model Number of an SPA Assembly

Standard Conax Packing Gland (PG) Compression Seal Fitting model numbers and configurations apply. Compression seal fittings are supplied loose unless otherwise indicated. **Example model number: SPA/PG5-500-A-T/500X120W(S304)-45-1-36** 



Product Name	Sealing Gland Used* if none indicate 'X'	Tube OD	Tube Wall	Tube Material (S304, S316, M405, HC276, I600)	"A" Tube End Angle (90°, 60°, 45°or 30°)	"B" Dimension (1/4" increments 1 = 1/4")	"L" Overall Tube Length (inches)
SPA	PG5-500-A-T	500	120W	(\$304)	45	1	36

#### **Standard Tube Sizes**

OD	WALL	(mm)	ID (	mm)	MATERIAL	OD	WALL	(mm)	ID (	mm)	MATERIAL	OD	WALI	L (mm)	ID (	mm)	MATERIAL	OD	WALL	. (mm)	ID (I	nm)	MATERIAL
(mm)						(mm)						(mm)						(mm)					
	.025″	(.64)	.200″	(5.08)	S304		.040″	(1.02)	.295″	(7.49)	S304		.035″	(.89)	.430″	(10.92)	S304	.625″	.065″ (1.65	(4.45)	105"	(4.9.52)	S304
.250″	.035″	(.89)	.180″	(4.57)	S304		.065″	(1.65)	.245″	(6.22)	S304		.049″	(1.25)	.402″	(10.21)	S304	(15.88)		(1.65)	.495 (12.53)	(12.53)	S316
	.025″	(.64)	.200″	(5.08)	S316		.040″	(1.02)	.295″	(7.49)	S316	500%	065″	(1.65)	375″	(9.53)	\$304		095″	(2.41)	560″	(14.22)	\$316
(6.35)	035″	(89)	180″	(4 57)	\$316	.375″	0.50%	(4, 47)	250#	(( 50)	6246		.005	(1.05)	.575	().55)	3301	.750″	.075	(2.71)	.500	(17.22)	5510
· /	.035	(.07)	.100	(4.57)	3310	(9.53)	.058″	(1.47)	.259"	(6.58)	\$316 .500"	.500	.120″	(3.05)	.260″	(6.60)	S304	(19.05)	.065″	(1.65)	.620″	(15.75)	MONEL 400
	.035″	(.89)	.180″	(4.57)	MONEL 400	().55)	065"	(1.65)	245"	(6.22)	MONEL 400	(12.70)		. ,		· ,			.005 (1.0.	(1105)	,	(15175)	
	0.25%	( 00)	100//	(4.57)			.005	(1.05)	.245	(0.22)	WONLL 400		.049″	(1.25)	.402″	(10.21)	S316	1.000″					
	.035″	(.89)	.180~	(4.57)	HASI C276		035″	(.89)	305″	(7.75)	HAST C276							(75 40)	.120″	(3.05)	.760″	(19.30)	S316
*Tubin	*Tubing is seemless o		orwel	ded and	halconnet		.000	(.0))	.505	(113)	111101 027 0		.065″	(1.65)	.370″	(9.40)	MONEL 400	(25.40)					
rubing	rubing is searchess of welded and armealed						.065″	(1.65)	.245″	(6.22)	HAST C276												
								( /		、,			.049″	(1.25)	.402″	(10.21)	HAST C276						

#### **Conax PG Compression Seal Fittings**

	SAMP	LE PRO	BE DIA	. / TUBII	NG (MM	)			SAMPLE PROBE DIA. / PIPE (MM)									
Model	NPT Size	0.250 (6.35)	0.375 (9.53)	0.500 (12.70)	0.625 (15.88)	0.750 (19.05)	1.000 (25.40)	1/8" .405" OD (10.29)	1/4" .54" OD (13.72)	3/8" .675" OD (17.15)	1/2" .84" OD (21.34)	3/4" 1.05" OD (26.67)	1" 1.315" OD (33.40)	1.25" 1.66" OD (42.16)	1.50" 1.90" OD (48.25)			
PG2	1/4"	Х																
PG4	1 /0"	Х	Х					Х										
PG5(PTM4)	1/2	Х	Х	Х				Х	Х									
PG5	3/4"	Х	Х	Х	Х	Х		Х	Х	Х								
PG5(PTM6)	1"	Х	Х	Х	Х	Х		Х	Х	Х								
PG6						Х	Х				Х							
PG7	1-1/4"										Х	Х	Х					
PG8	1-1/2"												Х					
PG9	2"													Х	Х			

Other sizes and materials available on request.\* All Conax PG fittings are available with an optional welded or threaded ASME/ANSI Rased Face Flange mount.

2300 Walden Avenue, Buffalo, New York 14225

+1 800 223 2389(P) | +1 716 684 7433(F) Conax@ConaxTechnologies.com

Bulletin 6066DS, Rev D' ©2021 Conax Technologies 6/21 Made in U.S.A.

