

2-Wire Transmitter with HART® Protocol

Model 5335D

- RTD, TC, Ohm, or mV Input
- Extremely High Measurement Accuracy
- HART® Communication
- 1.5 kVAC Galvanic Isolation
- Complies with European ATEX and CSA/FM Requirements for Hazardous Location Installation



Application:


- Linearized temperature measurement with Pt100...Pt1000, Ni100...Ni1000, or TC sensor.
- Difference or average temperature measurement of 2 sensor inputs.
- Conversion of linear resistance variation to a standard analog current signal.
- Amplification of a bipolar mV signal to a standard 4...20 mA current signal.
- Connection of up to 15 transmitters to a digital 2-wire signal with HART® communication.

Technical Characteristics:

- Within seconds the user can program a 5335D to measure temperatures within all standard ranges.
- The RTD and resistance inputs have cable compensation for 2-, 3- and 4-wire connection.
- Continuous check of vital stored data.
- Sensor error detection according to the guidelines in NAMUR NE 89.

Mounting/Installation:


- DIN Form B sensor head compatible.
- Supplied with 2 x M4 screws on a 33 mm (1.3") BC (optional 6-32 screws available).



Ideas. Solutions. Success.

Specifications

Order: 5335D



Electrical Specifications

Specifications Range:

-40°C to +85°C

Common Specifications:

Supply voltage.....8.0...30 VDC
 Voltage drop.....8.0 VDC
 Isolation voltage, test / operation1.5 kVAC / 50 VAC
 Warm-up time.....5 min.
 Communications interfaceLoop Link & HART*
 Signal / noise ratio.....Min. 60 dB
 Signal dynamics, input.....22 bit
 Signal dynamics, output.....16 bit
 Calibration temperature20...28°C

Accuracy, the greater of general and basic values:

General Values		
Input Type	Absolute Accuracy	Temperature Coefficient
All	≤ ±0.05% of span	≤ ±0.005% of span / °C

Basic Values		
Input Type	Basic Accuracy	Temperature Coefficient
Pt100 and Pt1000	≤ ± 0.1°C	≤ ±0.005°C/°C
Ni100	≤ ± 0.2°C	≤ ±0.005°C / °C
Lin. R	≤ ± 0.1 Ω	≤ ± 5 mΩ/°C
Volt	≤ ±10 μV	≤ ± 0.5 μV/°C
TC type: E, J, K, L, N, T, U	≤ ±0.5°C	≤ ±0.025°C/°C
TC type: B, R, S, W3, W5	≤ ±1°C	≤ ±0.1°C/°C

EMC immunity influence < ±0.1% of span	
Extended EMC immunity: NAMUR NE 21, A criterion, burst < ±1% of span	

Vibration.....IEC 60068-2-6 Test FC
 Lloyd's specification no. 1.....4 g / 2...100 Hz
 Max. wire size.....1 x 1.5 mm² (16 AWG)
 stranded wire
 Humidity.....< 95% RH (non-cond.)
 Dimensions.....Ø 44 x 20.2 mm
 Protection degree (encl. / terminal).....IP68 / IP00

Electrical Specifications, Input:

Max. offset.....50% of selected max. value

RTD and Linear Resistance Input:

RTD Type	Min. Value	Max. Value	Min. Span	Standard
Pt100	-200°C	+850°C	10°C	IEC 60751
Ni100	-60°C	+250°C	10°C	DIN 43760
Lin. R	0 Ω	7000 Ω	10 Ω	-----

Cable resistance per wire (max.).....5 Ω
 Sensor current.....Nom. 0.2 mA

Voltage input:

Measurement range.....-800...+800 mV
 Min. span2.5 mV
 Input resistance.....10 MΩ

TC Input:

Type	Min. Temperature	Max. Temperature	Min. Span	Standard
B	+400°C	+1820°C	100°C	IEC584
E	-100°C	+1000°C	50°C	IEC584
J	-100°C	+1200°C	50°C	IEC584
K	-180°C	+1372°C	50°C	IEC584
L	-100°C	+900°C	50°C	DIN 43710
N	-180°C	+1300°C	50°C	IEC584
R	-50°C	+1760°C	100°C	IEC584
S	-50°C	+1760°C	100°C	IEC584
T	-200°C	+400°C	50°C	IEC584
U	-200°C	+600°C	50°C	DIN 43710
W3	0°C	+2300°C	100°C	ASTM E988-90
W5	0°C	+2300°C	100°C	ASTM E988-90

Cold junction compensation.....< ±1.0°C

Current Output:

Signal range4...20 mA
 Min. signal range.....16 mA
 Updating time.....440 ms
 Load resistance.....≤ (Vsupply - 8) / 0.023 [Ω]

Sensor Error Detection:

Programmable3.5...23 mA

EEEx / I.S. Approval*:

KEMA 03ATEX1537 X II 1 GD, T80°C...T105 °C
 EEx ia IIC T6 / T4
 Max. amb. temperature for T1..T485°C
 Max. amb. temperature for T5 og T660°C
 ATEX, applicable in zone.....0, 1, 2, 20, 21 or 22
 FM, applicable in*.....IS, Cl. I, Div. 1, Gr. A, B, C, D
 IS, Cl. I, Zone 0, AEx ia IIC
 FM Installation Drawing No.5300Q502
 CSA, applicable in*IS, Cl. I, Div. 1, Gr. A, B, C, D
 Ex ia IIC
 IS, Cl. I, Zone 0, AEx ia IIC
 CSA, Installation Drawing No.533XQC03
 INMETRO 09/UL-BRCO-0002*BR-Ex ia IIC T4 or T6 or
 -40°C ≤ Tamb. ≤ +85°C, or
 -40°C ≤ Tamb. ≤ +60°C

Ex / I.S. Data*:

U_i.....: 30 VDC
 I_i.....: 120 mA DC
 P_i.....: 0.84 W
 L_i.....: 10 μH
 C_i.....: 1.0 nF

Marine Approval*:

Det Norske Veritas, Ships & Offshore.....Stand. for Certic. No. 2.4

GOST R Approval*.....Certificate available upon request.

Observed Authority Requirements: Standard:

EMC 2004/108/ECEN 61326-1
 ATEX 94/9/ECEN 50014, EN 50020,
 EN 50281-1-1, EN 50284
 FM.....3600, 3611, 3610
 CSA, CAN / CSAC22.2 No. 157,
 E60079-11, UL 913
 INMETRO.....IEC 60079-0, IEC 60079-11

Of span = Of the presently selected range

Loop Link = PC compatible programming software

IS = Intrinsically Safe

*The transmitter is manufactured by PR electronics. All approvals listed are recognized under the PR name.

2300 Walden Avenue, Buffalo, New York 14225

+1 800 223 2389 (P) | +1 716 684 7433 (F)

conax@conaxtechnologies.com

Bulletin 6081, Rev B ©2020 Conax Technologies 11/20



ConaxTechnologies.com

