



Type C Thermocouple Reference Tables (Celsius)

<u>Thermoelectric Voltage in Millivolts</u>												
°C	0	1	2	3	4	5	6	7	8	9	10	°C
2100	34.849	34.860	34.871	34.883	34.894	34.905	34.917	34.928	34.939	34.951	34.962	2100
2110	34.962	34.973	34.984	34.996	35.007	35.018	35.029	35.041	35.052	35.063	35.074	2110
2120	35.074	35.085	35.097	35.108	35.119	35.130	35.141	35.152	35.164	35.175	35.186	2120
2130	35.186	35.197	35.208	35.219	35.230	35.241	35.252	35.263	35.274	35.285	35.296	2130
2140	35.296	35.307	35.318	35.329	35.340	35.351	35.362	35.373	35.384	35.395	35.406	2140
2150	35.406	35.417	35.428	35.439	35.450	35.461	35.472	35.482	35.493	35.504	35.515	2150
2160	35.515	35.526	35.537	35.547	35.558	35.569	35.580	35.591	35.601	35.612	35.623	2160
2170	35.623	35.634	35.644	35.655	35.666	35.676	35.687	35.698	35.708	35.719	35.730	2170
2180	35.730	35.740	35.751	35.762	35.772	35.783	35.793	35.804	35.814	35.825	35.836	2180
2190	35.836	35.846	35.857	35.867	35.878	35.888	35.899	35.909	35.920	35.930	35.940	2190
2200	35.940	35.951	35.961	35.972	35.982	35.993	36.003	36.013	36.024	36.034	36.044	2200
2210	36.044	36.055	36.065	36.075	36.086	36.096	36.106	36.116	36.127	36.137	36.147	2210
2220	36.147	36.157	36.168	36.178	36.188	36.198	36.208	36.219	36.229	36.239	36.249	2220
2230	36.249	36.259	36.269	36.279	36.289	36.300	36.310	36.320	36.330	36.340	36.350	2230
2240	36.350	36.360	36.370	36.380	36.390	36.400	36.410	36.420	36.430	36.440	36.449	2240
2250	36.449	36.459	36.469	36.479	36.489	36.499	36.509	36.519	36.528	36.538	36.548	2250
2260	36.548	36.558	36.568	36.577	36.587	36.597	36.607	36.616	36.626	36.636	36.645	2260
2270	36.645	36.655	36.665	36.675	36.684	36.694	36.703	36.713	36.723	36.732	36.742	2270
2280	36.742	36.751	36.761	36.771	36.780	36.790	36.799	36.809	36.818	36.828	36.837	2280
2290	36.837	36.846	36.856	36.865	36.875	36.884	36.894	36.903	36.912	36.922	36.931	2290
2300	36.931	36.940	36.950	36.959	36.968	36.978	36.987	36.996	37.005	37.015	37.024	2300
2310	37.024	37.033	37.042	37.051	37.061	37.070						2310

Reference ASTM E988.

Temperature in Degrees °C, reference junction at 0°C.

"W5" Conax Designation, not ANSI/ASTM