



100 Ohm Platinum RTD Resistance vs. Temperature Tables Alpha=.003916 (Celsius)

°C	0	-1	-2	-3	-4	-5	-6	-7	-8	-9	-10	°C
-200	17.14											-200
-190	21.46	21.03	20.59	20.16	19.73	19.29	18.86	18.43	18.00	17.57	17.14	-190
-180	25.80	25.37	24.93	24.50	24.07	23.63	23.20	22.76	22.33	21.90	21.46	-180
-170	30.12	29.69	29.26	28.83	28.40	27.97	27.53	27.10	26.67	26.24	25.80	-170
-160	34.42	33.99	33.56	33.13	32.70	32.28	31.85	31.42	30.99	30.56	30.12	-160
-150	38.68	38.26	37.83	37.41	36.98	36.55	36.13	35.70	35.27	34.85	34.42	-150
-140	42.91	42.49	42.07	41.64	41.22	40.80	40.38	39.95	39.53	39.10	38.68	-140
-130	47.11	46.69	46.27	45.85	45.43	45.01	44.59	44.17	43.75	43.33	42.91	-130
-120	51.29	50.87	50.45	50.04	49.62	49.20	48.78	48.37	47.95	47.53	47.11	-120
-110	55.44	55.02	54.61	54.19	53.78	53.36	52.95	52.53	52.12	51.70	51.29	-110
-100	59.57	59.16	58.74	58.33	57.92	57.50	57.09	56.68	56.26	55.85	55.44	-100
-90	63.68	63.27	62.86	62.45	62.04	61.63	61.21	60.80	60.39	59.98	59.57	-90
-80	67.77	67.36	66.96	66.55	66.14	65.73	65.32	64.91	64.50	64.09	63.68	-80
-70	71.85	71.44	71.04	70.63	70.22	69.81	69.41	69.00	68.59	68.18	67.77	-70
-60	75.91	75.51	75.10	74.70	74.29	73.88	73.43	73.07	72.66	72.26	71.85	-60
-50	79.96	79.56	79.15	78.75	78.34	77.94	77.53	77.13	76.72	76.32	75.91	-50
-40	83.99	83.59	83.19	82.79	82.38	81.98	81.58	81.17	80.77	80.36	79.96	-40
-30	88.01	87.61	87.21	86.81	86.41	86.01	85.60	85.20	84.80	84.40	83.99	-30
-20	92.02	91.62	91.22	90.82	90.42	90.02	89.62	89.22	88.82	88.42	88.01	-20
-10	96.02	95.62	95.22	94.82	94.42	94.02	93.62	93.22	92.82	92.42	92.02	-10
0	100.00	99.60	99.20	98.81	98.41	98.01	97.61	97.21	96.81	96.42	96.02	0
°C	0	-1	-2	-3	-4	-5	-6	-7	-8	-9	-10	°C
°C	0	1	2	3	4	5	6	7	8	9	10	°C
0	100.00	100.40	100.80	101.19	101.59	101.99	102.38	102.78	103.18	103.57	103.97	0
10	103.97	104.37	104.76	105.16	105.56	105.95	106.35	106.74	107.14	107.53	107.93	10
20	107.93	108.32	108.72	109.11	109.51	109.90	110.30	110.69	111.09	111.48	111.88	20
30	111.88	112.27	112.66	113.06	113.45	113.84	114.24	114.63	115.02	115.42	115.81	30
40	115.81	116.20	116.59	116.99	117.38	117.77	118.16	118.56	118.95	119.34	119.73	40
50	119.73	120.12	120.51	120.91	121.30	121.69	122.08	122.47	122.86	123.25	123.64	50
60	123.64	124.03	124.42	124.81	125.20	125.59	125.98	126.37	126.76	127.15	127.54	60
70	127.54	127.93	128.32	128.71	129.09	129.48	129.87	130.26	130.65	131.04	131.42	70
80	131.42	131.81	132.20	132.59	132.98	133.36	133.75	134.14	134.52	134.91	135.30	80
90	135.30	135.68	136.07	136.46	136.84	137.23	137.62	138.00	138.39	138.77	139.16	90



100 Ohm Platinum RTD
Resistance vs. Temperature Tables
Alpha=.003916
 (Celsius)

°C	0	1	2	3	4	5	6	7	8	9	10	°C
100	139.16	139.55	139.93	140.32	140.70	141.09	141.47	141.86	142.24	142.63	143.01	100
110	143.01	143.39	143.78	144.16	144.55	144.93	145.31	145.70	146.08	146.46	146.85	110
120	146.85	147.23	147.61	148.00	148.38	148.76	149.15	149.53	149.91	150.29	150.67	120
130	150.67	151.06	151.44	151.82	152.20	152.58	152.96	153.35	153.73	154.11	154.49	130
140	154.49	154.87	155.25	155.63	156.01	156.39	156.77	157.15	157.53	157.91	158.29	140
150	158.29	158.67	159.05	159.43	159.81	160.19	160.57	160.95	161.33	161.70	162.08	150
160	162.08	162.46	162.84	163.22	163.60	163.97	164.35	164.73	165.11	165.48	165.86	160
170	165.86	166.24	166.62	166.99	167.37	167.75	168.12	168.50	168.88	169.25	169.63	170
180	169.63	170.00	170.38	170.76	171.13	171.51	171.88	172.26	172.63	173.01	173.38	180
190	173.38	173.76	174.13	174.51	174.88	175.26	175.63	176.01	176.38	176.75	177.13	190
200	177.13	177.50	177.88	178.25	178.62	179.00	179.37	179.74	180.12	180.49	180.86	200
210	180.86	181.23	181.61	181.98	182.35	182.72	183.09	183.47	183.84	184.21	184.58	210
220	184.58	184.95	185.32	185.70	186.07	186.44	186.81	187.18	187.55	187.92	188.29	220
230	188.29	188.66	189.03	189.40	189.77	190.14	190.51	190.88	191.25	191.62	191.99	230
240	191.99	192.36	192.73	193.09	193.46	193.83	194.20	194.57	194.94	195.31	195.67	240
250	195.67	196.04	196.41	196.78	197.14	197.51	197.88	198.25	198.61	198.98	199.35	250
260	199.35	199.71	200.08	200.45	200.81	201.18	201.55	201.91	202.28	202.64	203.01	260
270	203.01	203.38	203.74	204.11	204.47	204.84	205.20	205.57	205.93	206.30	206.66	270
280	206.66	207.02	207.39	207.75	208.12	208.48	208.85	209.21	209.57	209.94	210.30	280
290	210.30	210.66	211.03	211.39	211.75	212.11	212.48	212.84	213.20	213.56	213.93	290
300	213.93	214.29	214.65	215.01	215.37	215.74	216.10	216.46	216.82	217.18	217.54	300
310	217.54	217.90	218.26	218.63	218.99	219.35	219.71	220.07	220.43	220.79	221.15	310
320	221.15	221.51	221.87	222.23	222.59	222.94	223.30	223.66	224.02	224.38	224.74	320
330	224.74	225.10	225.46	225.81	226.17	226.53	226.89	227.25	227.61	227.96	228.32	330
340	228.32	228.68	229.04	229.39	229.75	230.11	230.46	230.82	231.18	231.53	231.89	340
350	231.89	232.25	232.60	232.96	233.31	233.67	234.03	234.38	234.74	235.09	235.45	350
360	235.45	235.80	236.16	236.51	236.87	237.22	237.58	237.93	238.28	238.64	238.99	360
370	238.99	239.35	239.70	240.05	240.41	240.76	241.11	241.47	241.82	242.17	242.53	370
380	242.53	242.88	243.23	243.58	243.94	244.29	244.64	244.99	245.35	245.70	246.05	380
390	246.05	246.40	246.75	247.10	247.46	247.81	248.16	248.51	248.86	249.21	249.56	390
400	249.56	249.91	250.26	250.61	250.96	251.31	251.66	252.01	252.36	252.71	253.06	400
410	253.06	253.41	253.76	254.11	254.46	254.80	255.15	255.50	255.85	256.20	256.55	410
420	256.55	256.89	257.24	257.59	257.94	258.29	258.63	258.98	259.33	259.67	260.02	420
430	260.02	260.37	260.72	261.06	261.41	261.75	262.10	262.45	262.79	263.14	263.49	430
440	263.49	263.83	264.18	264.52	264.87	265.21	265.56	265.90	266.25	266.59	266.94	440



100 Ohm Platinum RTD
Resistance vs. Temperature Tables

Alpha=.003916

(Celsius)

°C	0	1	2	3	4	5	6	7	8	9	10	°C
450	266.94	267.28	267.63	267.97	268.31	268.66	269.00	269.35	269.69	270.03	270.38	450
460	270.38	270.72	271.06	271.41	271.75	272.09	272.44	272.78	273.12	273.46	273.80	460
470	273.80	274.15	274.49	274.83	275.17	275.51	275.86	276.20	276.54	276.88	277.22	470
480	277.22	277.56	277.90	278.24	278.58	278.92	279.26	279.61	279.95	280.29	280.63	480
490	280.63	280.96	281.30	281.64	281.98	282.32	282.66	283.00	283.34	283.68	284.02	490
500	284.02	284.36	284.69	285.03	285.37	285.71	286.05	286.39	286.72	287.06	287.40	500

Reference JIS C1604-1989